

# Olivetti MELIO P1300 Series



Olivetti SPA VIA JERVIS, 77 10015 IVREA (TO) ITALY [www.olivetti.com](http://www.olivetti.com)

Olivetti recommends Microsoft® Windows® Vista™  
Olivetti recommande Microsoft® Windows® Vista™

<b>MELIO P1300 Series</b>		
	<b>MELIO-P13XX-MT</b>	<b>MELIO-P13XX-SF</b>
Technology	Intel® 64 bit Dual Core	
	Intel® Core 2 Duo E5200 (2 MB L2 Cache, 2x 2.50 Ghz, 800 MHz FSB) Intel® Core 2 Duo E7300 (3 MB L2 Cache, 2x 2.66 Ghz, 1066 MHz FSB) Intel® Core 2 Duo E8400 (6 MB L2 Cache, 2x 3.00 Ghz, 1333 MHz FSB) Intel® Core 2 Quad Q8200 (4 MB L2 Cache, 4x 2.33 Ghz, 1333 MHz FSB) Intel® Core 2 Quad Q9400 (6 MB L2 Cache, 4x 2.66 Ghz, 1333 MHz FSB)	
Operating system	Genuine Windows® XP Professional - Genuine Windows® Vista™ Home / Premium / Business - Linux OS	
Software	Symantec Norton® AntiVirus 2007, Nero® Suite 6, Acrobat® Reader 5, ...	
Chipset	Intel® G31 Express chipset	
Memory	Dual Channel memory from 1 GB to 4 GB DDR2 667 MHz PC2-5300	
Hard drive(s)	250, 320 GB GB SATA 3.0 GB/s hard drive (7200 rpm)	
Optical drive (s)	DVD/RW 18x Dual-Layer	
Removable media	20-in-1 Media Card Reader Optional Floppy 3.5" HD	
Expansion bays	Internal : 2x 3.5" External : 2x 5.25" and 2x 3.5"	Internal : 1x 3.5" External : 1x 5.25" and 1x 3.5"
Expansion slots	2 full-height PCI 1 full-height PCI-Express x1 1 full-height PCI-Express x16	2 low-profile PCI 1 low-profile PCI-Express x1 1 low-profile PCI-Express x16
Memory slots	2 DIMMs	
Graphics	Integrated 3D Intel® GMA-X3100 Graphics with 256 MB Dynamic-Shared Memory	
Audio	Integrated Intel® High Definition Audio 5.1 Channel 3D Compatible	
Communications	Integrated Gigabit LAN 32 bits NIC 10/100/1000 Mb/s	
Rear I/O ports and connectors	4 USB 2.0 ports, 1 Serial, 1 parallel, 1 VGA port, 2 PS/2 ports (mouse and keyboard), 1 RJ-45 port, 3 audio in/out	
Front I/O ports and connectors	2 USB 2.0 ports, 2 audio headphone and microphone jacks	
Input device	Multimedia keyboard and Optical 2-Button scroll mouse available as PS/2 or USB	
Monitors	TFT Multimedia Wide 15.4", 17", 19" or 22"	
Security	Kensington lock support (optional)	
Chassis	Medium-tower form factor	Small Form Factor
Power	300-watt PFC Power Supply	240-watt passive PFC Power Supply
Dimensions (WxDxH)	180 x 430 x 480 mm	320 x 430 x 100 mm
Warranty	2 years	

